AmTryke®

The therapeutic tricycle for children with disabilities

For questions or to place an order, please contact:

AmTryke, LLC.
Phone: (888) - AMTRYKE ext. 14
Email: amtryke@ambucs.org
Visit our website: www.ambucs.org

Assembly Instructions

AM-12 and AM-16 Chain Tensioner Instructions

In the event that the chain on the AM-12 or AM-16 should come loose or fall off please follow the directions.

Tools needed for this: Phillips head screw driver

1) Using the Phillips head screw driver remove the two screws on the outside of the chain guard that secure it. The chain guard is a long grey plastic piece on the front of the tryke.
2) Position the foot crank arm in the following position. Refer to below picture.

Chain Guard

Silver arm attached to pedal is the crank arm.

3) Using your figures carefully pull on the bottom of the chain guard cover as it will come loose.

4) Turn the crank arm (Pedals) 180 degrees until the upper crank arm (hand area) is pointint straight up on the same side as the chain guard. Chain guard can now be removed from top.

5) *This step is for tightening the chain if loose.* You will see the chain tensioner (see picture) located on each side of the chain tensioner is a Phillips head screw. Using the Phillips head screw driver loosen the two screws (Do Not Remove) so that the chain tensioner can be repositioned..

Phillips Head Screw

Chain Tensioner Sprocket

6) Using your hand push the chain tensioner inwards towards the front of the bike until the chain is tight. While still applying pressure to the tensioner tighten the two Phillips head screws using the Phillips head screw driver.

Reverse steps 1 thru 4 to reinstall chain guard.

AmTryke®

The therapeutic tricycle for children with disabilities

For questions or to place an order,
please contact:

AmTryke, LLC.
Phone: (888) - AMTRYKE ext. 14
Email: amtryke@ambucs.org
Visit our website: www.ambucs.org

Assembly Instructions

Follow the below instructions if the chain has come off

1) Put both the hand crank arm and foot crank arm in the same vertical position on the same side.
2) Place the chanin over the upper sprocket using your hands. **See Image 1A below**.
3) Place chain around lower sprocket using your hands. **See Image 1B below**.
4) Loosen tensioner. **Follow Step 5**
5) Place chain around tensioner. **See Image 1C below**.
6) Adjust chain tensioner. **Follow step 6**.
7) Reinstall chain guard. **Reverse steps 1 thru 4**.

Image 1A   **Image 1B**   **Image 1C**