



Assembly Instructions

Head Rest

Part Number 30-14-0330

Works with 1400 Seatback Set #30-13-1400 only

Contents of Head Rest

Padded Head Support
Adjustable Vertical Support Rod
Head Support Bracket
Horizontal Head Support Rod
Head Support Retaining Ring
Three Hex Head Screws

Tools Needed

3 mm Allen Wrench
Rubber Mallet



Installation Instructions

- 1) Remove caregiver handle from the top of 1400 seat back support rods. Use a rubber mallet to tap upwards if needed to remove handle.



2) Slide head support bracket over 1400 seat back support rods.



3) Loosen adjustment knob on head support bracket. Slide vertical head support rod through the center of the support bracket as shown.



4) Slide head support retaining ring over horizontal support rod as shown.



5) Insert the horizontal support rod through vertical support rod. The rounded end should be pointing towards the front of the bike.



6) Place padded head support against rounded end of horizontal support rod, align three holes in retaining ring with three holes in padded head support. Install three screws loosely by hand. Tighten using 3mm allen wrench securely once proper position for rider's head is determined.



7) Reinstall caregiver handle.

8) Adjust head rest to rider's height.

NOTE: BEFORE PLACING A CHILD ON THE TRYKE AFTER INSTALLING THE HEAD REST SUPPORT CHECK THAT ALL SCREWS AND KNOBS ARE TIGHT.



Contents of Head Rest

Padded Head Support

Adjustable Vertical Support Rod

Horizontal Head Support Rod

Head Support Bracket

Head Support Retaining Ring

Three Hex Head Screws